




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 33/38, 41/04	A1	(11) International Publication Number: WO 96/21599 (43) International Publication Date: 18 July 1996 (18.07.96)
(21) International Application Number: PCT/US95/14546 (22) International Filing Date: 13 November 1995 (13.11.95) (30) Priority Data: 08/336,980 10 November 1994 (10.11.94) US (71) Applicant: JEBCO PACKAGING SYSTEMS, INC. [US/US]; 2156 Flintstone Drive, Tucker, GA 30084 (US). (71)(72) Applicant and Inventor: BUCHANAN, Jerry, E. [US/US]; 3396G Fairway Oaks Drive, Lawrenceville, GA 30244 (US). (74) Agent: KENNEDY, Robert, B.; Kennedy & Kennedy, Suite 1250, 400 Northpark Town Center, 1000 Abernathy Road, Atlanta, GA 30328 (US).		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: FITMENT FOR FLEXIBLE CONTAINERS**(57) Abstract**

A fitment (20) for a container of the type having sides made of flexible heat sealable material has a tubular neck (21). A cap may be secured to an upper portion of the neck using threads (23). A heat sealable skirt (22), to which the container sides may be heat sealed, depends from an outwardly flared portion (25). The skirt has a heat sealable outer surface and a material thickness less than the material thickness of the neck.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

5

10

FITMENT FOR FLEXIBLE CONTAINERSTECHNICAL FIELD

This invention relates to closure fitments for flexible containers.

15

BACKGROUND OF THE INVENTION

20

Containers for liquids and fungibles, such as various consumer and household products, are commonly in the form of rigid bottles such as those made of glass and blow molded plastic. These are commonly constructed with tubular necks which, when capped, provide a closure. The necks and caps are usually threaded although some are constructed with clip on and press on caps.

25

30

Recently containers have been developed that are made of thin, flexible material, principally plastic film. In order to provide a firm structure to which a cap may be secured, such flexible containers are provided with fitments. Exemplary of these fitments is that shown in U.S. Patent No. 5,348,525. This fitment basically is a tube having a threaded neck on which a cap may be threaded and an enlarged, grooved base to which the container film is heat sealed. The top edge of the container itself extends linearly and laterally from the fitment base. Another fitment design for a flexible container has a

-2-

threaded tubular neck from the bottom of which a large, curved base extended. It is sealed in an upper corner of the container to provide a pour spout when the container is tilted manually with a container handle.

5 The just described fitments have had certain distinct problems. For example, they have been difficult to heat seal in place in an efficient manner due to their having to be relatively thick in order to provide sufficient body on which to secure a cap. They also have been difficult to
10 seal without creating wrinkles in the thin container film. This is particularly true where the shape of the container in the region adjacent the fitment is curved. In addition, their substantially cylindrical external shape has made it difficult to hold them in place during on line sealing
15 operations without axial slippage or rotation.

 Accordingly, it is seen that a need exists for a fitment for flexible containers that alleviates the just described problems. It is to the provisions of such that the present invention is primarily directed.

20

SUMMARY OF THE INVENTION

 In a preferred form of the invention a fitment for a container of the type having a body made of flexible heat sealable material has a tubular neck upon an upper portion
25 of which a cap may be secured. The neck also has a lower portion from which heat sealable skirt depends and to which the container body may be heat sealed. The skirt has a heat sealable outer surface and a material thickness less than the material thickness of the neck.

30 In another preferred form of the invention a fitment for a container of the type having a body made of flexible heat sealable material has a tubular neck with an upper portion on which a cap may be secured, an intermediate support portion, and a lower portion that flares outwardly
35 from the intermediate support portion. A heat sealable

-3-

skirt depends from the neck lower portion to which the flexible container body may be heat sealed.

BRIEF DESCRIPTION OF THE DRAWING

5 Figs. 1-5 illustrate, in perspective, a sequence of steps taken in mounting fitments that embody principles of the present invention to the bodies of flexible containers.

Figs. 6-7 illustrate from two different perspective views of the finished container with fitment attached.

10 Fig. 8 is a perspective view of a flexible handling and transport device in a configuration for receiving a flexible container.

15 Fig. 9 is a perspective view of the flexible handling and transport device of Fig. 8 in a container held configuration holding a flexible container by its fitment.

Figs. 10-14 show in greater detail the sequence of steps taken in sealing the fitment to the body of the container.

20 Fig. 15 is a cross sectional view of the fitment.

DETAILED DESCRIPTION

25 With references next to the drawing, and initially to Fig. 15 in particular, a fitment 20 is shown that embodies principles of the invention in a preferred form. The fitment is of unitary, plastic construction and has a tubular neck 21 and a flared skirt 22. The tubular neck has an upper portion 21 with external threads 23 and an outwardly flared lower portion 25. It also has a support portion 26 intermediate the upper and lower portion which includes a flange or protrusion 27 with an hexagonally shaped periphery.

30 The bottom end of the neck lower portion 25 is formed with an annular lip 28. The flared skirt 22 depends from the end of the neck lower portion inside of its lip 28. Here the skirt flares outwardly from the neck at an acute

angle a with respect to the axis x of the tubular fitment. Although this angle varies generally to match the shape of the flexible container in the area about the fitment, the angle shown here is about 13°, rendering it suitable for the container shaped as shown in the other figures. Although the angle a may be from 0° to 90° i.e. to the very boundaries of the definition of acute angle, preferably it is between these limits.

The fitment is preferably made of low density polyethylene. The container itself may be made of a flexible polyethylene film. The skirt 22 has a thin wall with respect to that of the neck 21, the skirt here varying from 15 mils at its open end distal the neck to 20 mils at its proximal end. The wall thickness of the neck lower portion is 33 mils here. The rest of the neck has variable wall thicknesses in excess of this.

The thinness of the skirt 22 enables a high quality heat seal to be made to the container material efficiently in minimal time, typically 0.75 seconds. This enables it to be sealed in economically viable, high speed manufacturing operations. The angled flare to the skirt 22 renders it relatively easy to be sealed to the container without creating wrinkles as with bottles with a curved upper wall profile since the shape of the container over the skirt matches that of the skirt itself.

Figs. 1-5 illustrate a sequence of steps taken in sealing the fitments 20 to containers as the containers are themselves being made from a continuous web of thin, heat sealable, plastic film. In these figures the film is being advanced from right to left as indicated by the light arrows in each figure. The film has been formed into the general shape of a double walled T to have a partially formed container bottom 30 from which two principal, spaced, container sides 31 extend. As the film advances the two sides 31 are brought into positions straddling a

-5-

mandrel 34 in an array of three mandrels mounted to a support 35. The fitments 20 are mounted on movable positioning member 37.

5 With continued reference to Figs. 1-5 and also to Figs. 10-14, the mandrels and positioning members with fitments are now converged as indicted by the dark arrows in Figs. 1 and 10. This serves to seat the fitment skirt 22 on the mandrel 34 as shown in Fig. 2. Two heat sealing dies 39 with confronting, spaced, flat surfaces are then
10 converged upon the flexible film sides 31 straddling the mandrel, as shown best in Figs. 10 and 11. This creates two direct fitment emplacement seals 40 as shown in Figs. 3 and 11 between the sides 31 straddling the fitment. The mandrels and positioning members are then spread, the film
15 advanced and the mandrels and positioning members again converged. As shown in Figs. 4 and 12 this creates two a band seals between the film sides 31 and the fitment skirt 22. As this is done the presence of the fitment lip 28 prevents the container material from creeping onto the neck
20 lower portion 25.

Again the mandrels and supports are spread, the film web advanced, and the mandrels and supports converged whereupon a secondary, overlaid seal 42 is formed by heat sealing dies 44 as shown in Figs. 13 and 14. The fitment
25 20 is now fully sealed to the sides as shown in Figs. 6 and 7 forming a flexible container 44. Note that in these figures two side seals 45 have now also been formed that extend from the fitment seals 41 and 42.

30 With reference next to Figs. 8 and 9, a container transport module (CTM) or puck 50 is shown for use in transporting the flexible containers 44 with secured fitments 20 through various process stations as for testing, filling and the like. Fig. 8 shows the CTM with its two arms 51 in a spread apart, open configuration to
35 receive a container. These arms support two cantilevered,

-6-

5 mating grippers 52 with confronting, semi-hexagonal surfaces 54. With a container 44 positioned between the arms 51 the arms are converged as shown in Fig. 9. This brings the semi-hexagonal surfaces of the grippers into contact with the hexagonal flange 27 of the fitment. With the flange 27 being the thickest portion or strong point of the fitment, a firm and secure grip is established by the CTM on the container. The CTM may now be conveyed itself and thereby transport the container suspended from the grippers 52, without the container being able to rotate, through various process stations.

10 It thus is seen that a fitment is now provided for flexible containers that alleviates problems associated with those of the prior art. It should be understood however that the embodiment just described in detail merely illustrates principles of the invention in its preferred form and that many modifications may be made thereto without departure from the spirit and scope of the invention as set forth in the following claims.

20

CLAIMS

1. A fitment for a container of the type having a body made of flexible heat sealable material, and with the fitment having a tubular neck upon an upper portion on which a cap may be secured and a lower portion, and a heat sealable skirt that depends from said neck lower portion to which the container body may be heat sealed, said skirt having a heat sealable outer surface and a material thickness less than the material thickness of said neck.

2. The fitment of claim 1 wherein said neck upper portion is threaded.

3. The fitment of claim 1 wherein said tubular neck has a support portion intermediate said neck upper portion and said neck lower portion this is configured to be gripped by ancillary container handling apparatus.

4. The fitment of claim 3 wherein said neck support portion has a plurality of flat sides configured to be gripped and restrained from rotating by ancillary mating container handling apparatus.

5. The fitment of claim 3 wherein at least part of said neck support portion has a material thickness greater than the material thickness of said neck upper and lower portions.




6. The fitment of claim 1 wherein said skirt flares conically outwardly from said neck lower portion.





7. The fitment of claim 6 wherein said tubular neck has an axis, and wherein said skirt flares conically outwardly from said neck lower portion at an acute angle.



8. The fitment of claim 7 wherein said tubular neck lower portion flares conically outwardly from said axis.




9. A fitment for a container of the type having a body made of flexible heat sealable material, and with the fitment having a tubular neck with an upper portion on which a cap may be secured, an intermediate support portion, and a lower portion that flares outwardly from said intermediate support portion; and a heat sealable skirt that depends from said neck lower portion to which the flexible container body may be heat sealed.


10. The fitment of claim 9 wherein said skirt flares outwardly from said neck lower portion.





**FIG 8****FIG 9**



**FIG 15**

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/14546

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :B65D 33/38, 41/04

US CL :215/43; 222/107; 383/80, 95

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 215/43; 222/107, 215; 383/80, 94, 95, 96

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 4,415,085 (CLARKE ET AL.) 15 November 1983, See col. 7, lines 10-63	1-10
Y	US, A, 5,036,889 (PHERIGO) 06 August 1991, See col. 1, lines 48-56	1-10
Y	US, A, 4,142,630 (HAYES ET AL.) 06 March 1979, See Fig. 2	1-8

☐

Further documents are listed in the continuation of Box C.

☐

See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"A" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

22 FEBRUARY 1996

Date of mailing of the international search report

07.03.96

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

STEPHEN P. GARBE

Telephone No. (703) 308-1207

Sheila Veney
Sheila Veney
Paralegal Specialist
Group 3200